



101601.02

Screen

Screen LED

Floodlight adjustable projector.
Electronic driver included.

02 black



Installations

Adjustable LED Floodlight IP65.

Material

Body made of anodized powder coated aluminium alloy; bracket made of steel; screws made of stainless steel; flat screen made of transparent extra-clear tempered glass. Internal anti glare diffuser made of frosted PMMA.

Wiring

Complete with cord grip made of nickel-plated brass and with H05RN-F 3x1mm² L=300mm; power supply cable; integrated electronic 220-240V 50/60Hz driver.

Supply voltage: 220-240V 50/60 Hz

Photobiological Risk

Certified device in RISK GROUP 1 (Low Risk)-The lamp does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

Compliance

In accordance with standard: CEI EN 60598-1:2015 + A11:2009; IEC 60598-2:2015 2-1.

Sources

Type: LED
Color: white
Power: 20W
Color temperature: 3000K
MacAdam: 3 SDCM
CRI: >80
Nominal flux (Tc=25°C): 1900 lm
Lifespan (Ta=25°C): 30000h L80
Lamp included

Photometric data

Luminous flux (Ta=25°C): 1511 lm